

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ :
A21B 1/00, H05B 1/00, 3/10, H05K 5/00,
7/16, F26B 21/06

A1

(11) International Publication Number: **WO 00/21372**

(43) International Publication Date: 20 April 2000 (20.04.00)

(21) International Application Number: PCT/US99/23492

(22) International Filing Date: 8 October 1999 (08.10.99)

(30) Priority Data:
09/169,362 9 October 1998 (09.10.98) US

(71) Applicant: ERICSSON, INC. [US/US]; 7001 Development Drive, Research Triangle Park, NC 27709 (US).

(72) Inventor: JONES, Clifford; 12824 Lindley Drive, Raleigh, NC 27614 (US).

(74) Agent: COATS & BENNETT, P.L.L.C.; P.O. Box 5, Raleigh, NC 27602 (US).


(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: ELECTRONICS CABINET COOLING SYSTEM

(57) Abstract

A cabinet for housing telecommunications equipment in outdoor locations includes an enclosure (20) for containing the telecommunications equipment. A subrack (40) is mounted within the enclosure. A duct (56) directs ambient air from outside the cabinet to the subrack. A fan (80) draws ambient air into an inlet (52) through the duct through the subrack and out of the enclosure. A heater (62) is provided for heating inlet air when ambient temperatures are low.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

ELECTRONICS CABINET COOLING SYSTEM

Field of the Invention

The present invention relates generally to cabinets for electronic equipment and, more particularly, to a telecommunications cabinet for housing telecommunications equipment in outdoor locations.

Background of the Invention

Telecommunications equipment is typically designed for indoor temperature controlled environments, but is often deployed in outdoor locations. When telecommunications equipment is deployed in outdoor locations, a cabinet is typically used to provide environmental protection and control thermal conditions within the design limits of the telecommunications equipment.

There are essentially two main approaches to housing telecommunications equipment in outdoor cabinets – sealed cabinets and ventilated cabinets. Ventilating cabinets use natural or forced convection to draw ambient air through the cabinet to cool the equipment inside. Natural convection is only feasible for low density heat dissipation. At moderate and high power densities, forced ventilation is required.

Conventional cabinet ventilation systems use one or more fans to draw enough air into the cabinet to maintain the temperature below maximum equipment limits and to return the heated air to the outside environment. At low temperatures, the fans are turned off by a thermostat. In extremely cold climates, an electric heater is used to maintain the cabinet temperature within minimum equipment temperatures.

A drawback to the use of ventilated cabinets is that the control of the fans and heater is normally limited to on/off operation. This method of operation can lead to abrupt changes in temperature and create hot spots in the cabinet. In some cases, the equipment specifications limit the allowed rate of change in cooling air temperature to between 0.5 and 1.0° C per minute. Ordinarily, this rate of change cannot be guaranteed with conventional ventilated cabinets.

Sealed cabinets provide an alternative to ventilated cabinets for housing telecommunications equipment in outdoor locations. Sealed cabinets provide maximum protection from airborne contaminants, but require special attention to the task of removing heat dissipated by the equipment. A variety of methods are used for removing the heat dissipated by the telecommunications equipment. At moderate power densities, circulation fans, air-to-air heat exchangers, or heat pipes may be used. At high power densities, or for installations where the ambient temperature may exceed the equipment limit, an air-conditioner may be required. In extremely cold weather, electric heaters are often required to maintain the minimum equipment temperature. All of these methods for thermal conditioning have certain disadvantages or limitations.

Heat exchangers and heat pipes require a relatively large difference between the ambient temperature and the equipment cooling air temperature in order to properly transfer heat, thereby restricting the use of such an approach to cooler ambient environments. The use of air-conditioners to control temperature within sealed cabinets also presents difficulties. The heat load from the equipment in some

sealed cabinets is such that the air-conditioner is required to run even at low ambient conditions, sometimes as low as 0°F. Some units use variable speed-condenser blowers and/or a flooded condenser design to reduce the heat loss through the condenser and allow the air-conditioner to run at very low temperatures. Other units use a low-ambient vent to cool the cabinet with outside air when the temperature is too low to run the air conditioner. These solutions increase the cost and size of the cooling system. In addition, for small cabinets designed for locations with severe space limitations, using an air conditioner is a significant size penalty. Air conditioners are also a source of noise which may preclude their use in noise sensitive environments.

Summary of the Invention

The present invention is a telecommunications equipment cabinet particularly adapted for use in outdoor locations. The cabinet comprises an enclosure having an electronics subrack for containing the telecommunications equipment. The enclosure includes an inlet opening in a lower portion of the cabinet for drawing cool ambient air into the cabinet. An exhaust outlet for exhausting heated air is disposed in an upper portion of the cabinet. In the preferred embodiment, the cabinet includes a segregated air routing system to direct air from the inlet, through the subrack, and out of the cabinet. The segregated air routing system includes a duct that extends from the air inlet to a subrack plenum disposed directly below the electronics subrack. An exhaust plenum is disposed immediately above the subrack and communicates with the exhaust outlet.

One or more fans draw cool ambient air into the cabinet. The cool ambient air flows through the inlet to the subrack plenum. A heater in the inlet duct heats the air at low ambient temperatures. The air is then pulled through the electronics in the subrack where the air picks up heat dissipated by the equipment. From the subrack, the heated air enters the exhaust plenum and is expelled through the exhaust outlet. The air flow is confined by the duct work in the cabinet for more effective control of cooling air flow rate and temperature.

The cooling system includes a thermal controller for monitoring the temperature within the cabinet and for controlling the operation of the fan(s) and the heater. The thermal controller is typically a microprocessor-based controller that receives as input the subrack inlet air temperature, the subrack exit air temperature, subrack equipment temperature, and outdoor ambient air temperature. At low ambient temperatures (low temperature mode), the controller of the preferred embodiment causes the fans to operate at reduced capacity to maintain a nearly constant air flow through the subrack. The power to the heating element is varied to maintain the subrack inlet temperature constant over a predetermined temperature range up to a first predetermined temperature. In moderate temperatures, the power to the heating element is turned off and the air flow is increased non-linearly as the temperature increases so as to maintain the temperature at the subrack exit constant. At high temperatures, the fans operate at full capacity.

The cabinet of the present invention is able to cool the electronics in compliance with equipment requirements for cooling air temperature and rate of

temperature change without the burdens of size, complexity, power consumption, and noise of an air-conditioned cabinet. Protection from air-borne contaminants is provided by filters disposed in the inlet duct.

Brief Description of the Drawings

FIGURE 1 is a perspective view of the telecommunications cabinet of the present invention with the enclosure shown in hidden lines.

FIGURE 2 is a section view of the telecommunications cabinet.

FIGURE 3 is a front elevation view of the telecommunications cabinet.

FIGURE 4 is a block diagram of the control system for the telecommunication cabinet.

FIGURE 5 is a graph illustrating the theoretical and practical thermal envelopes for the telecommunications cabinet over a range of ambient temperatures.

FIGURE 6 is a graph illustrating the operation of the thermal control system for the telecommunications cabinet over a range of ambient temperatures.

FIGURE 7 is a graph illustrating the fan operation of one embodiment.

Detailed Description

An electronic equipment cabinet 10 includes various electronics housed within a suitable enclosure 20 having a top 22, a bottom 24, and sides 26. For purposes of illustration, the electronic equipment cabinet 10 will be described as housing telecommunications electronics 34 such as that required for a cellular telephone base station. Such electronic equipment cabinets 10 typically include both power

electronics 32 and communications electronics 34. The power electronics 32 are typically separated from the communications electronics 34 by a suitable power distribution box 30 so as to reduce the hazards associated with servicing the communications electronics 34. The communications electronics 34 typically include a variety of communication circuit modules 42. The circuit modules 42 typically take the form of removable circuit cards disposed in a vertical orientation and supported by an electronics subrack 40 within the cabinet enclosure 20. The particular details of the configuration and operation of the power electronics 32 and communications electronics 34 are well known to those skilled in the art and are not discussed further herein except as to assist in understanding the present invention.

When operating, the communications electronics 34 within the electronic equipment cabinet 10 should be cooled to help prevent malfunctions or damage; this is particularly true for electronic equipment cabinets 10 in locations that are not in temperature controlled environments, such as outdoor environments. The electronic equipment cabinet 10 of the present invention includes a cooling system 50 to cool the communications electronics 34. The cooling system 50 provides a flow of cooling air across the communications electronics 34. In general, the airflow is in via one or more inlet vents 52, through a inlet duct 56 to a subrack inlet plenum 70, through the electronics subrack 40 to an subrack exhaust plenum 72, and out one or more exhaust vents 74. At least one fan 80, and preferably a plurality fans 80, are disposed downstream from the electronics subrack 40 and pull external air along this airflow path.

In one embodiment, the inlet vent 52 is disposed along the bottom of the enclosure 20 and is guarded by a inlet grill 54 sized to keep out larger nesting and stinging insects and the like. Equivalently, the inlet vent 52 may be disposed along the sides 26 of the enclosure 20 near the bottom 24. The inlet duct 56 connects to the inlet vent 52 and includes a lower portion and an upper portion. The lower portion preferably includes a filter 58 and a heating chamber 60. The filter 58 helps remove airborne fibers and further helps control the ingress of insects. The heating chamber 60 includes one or more heating elements 62. The heating element 62 is used to preheat the cooling air entering from the outside when it is cold so that the air entering the subrack inlet plenum 70 is above the minimum cooling air temperature specified for the equipment. Preferably, the power density of the heating element 62 is limited, such as in the range of 6 watts per square inch of heater surface area or less, to minimize radiant heating of the electronics subrack 40 and other equipment within the radiation field of the heating element 62 and to avoid reaching flammability limits of adjacent components and/or foreign objects entrained in the airflow. The heating element 62 is preferably an electric resistance heater and is controlled by the thermal controller 100 as more fully described below. Preferably, the power for the heating element 62 is regulated by a triac 64 having on/off zero crossing detection so as to minimize electromagnetic interference on any associated AC power lines. The upper portion of the inlet duct 56 connects to the subrack inlet plenum 70. The subrack inlet plenum 70 is a generally open area, preferably disposed below the electronics

subrack 40, which is designed to distribute the air being supplied to the electronics subrack 40.

Air from the subrack inlet plenum 70 flows through the electronics subrack 40 so as to cool the communications electronics 34 therein. Typically, but not necessarily, the airflow is vertically through the electronics subrack 40, between the spaced apart circuit cards. Because the cooling system 50 of the present invention may not be equipped with humidity control, and to protect from other contamination, it may be advisable to employ conformal coatings, protective (but thermally conductive) barriers, sealants, or the like to keep airborne contaminants and moisture from direct contact with the communications electronics components.

Air from the electronics subrack 40 exits from the subrack into the subrack exhaust plenum 72. The subrack exhaust plenum 72 is a generally open area which collects the airflow from the electronics subrack 40 and channels it to the fans 80. The fans 80 pull the air through the electronics subrack 40 and exhaust the same to the outside through the exhaust vents 74. While only one fan 80 is required, it is preferred that a plurality of fans 80 be used to reduce overall size and provide redundancy in case of fan failure. The capacity and number of fans 80 should vary depending on the desired capacity of the cooling system 50. Each fan 80 should be variable speed over a wide range of speeds. Each fan 80 should be equipped with a backdraft damper to prevent recirculation of cooling air through any fans 80 that are not in use. To provide a redundant backup, it is preferred that one fan 80 be held in reserve. In the event that the optional fan speed sensors indicate that one of the main fans 80 is not

operating properly, such as when the detected speed is 75% or less than the desired speed, the reserve fan 80 may be substituted for the malfunctioning fan 80.

A thermal controller 100 controls the operation of the heating element 62 and the fans 80. The thermal controller 100 includes suitable control electronics, a plurality of temperature sensors 112, 114, 116, 118, and optional fan speed sensors 120 for each fan 80. The temperature sensors 112, 114, 116, 118 typically include a pair of subrack inlet temperature sensors 112, one primary and one backup, a subrack outlet temperature sensor 114, a subrack equipment temperature sensor 116 and an ambient air temperature sensor 118. The subrack inlet temperature sensors 112 should be located in the center of the subrack inlet plenum 70, downstream from the heating element 62 if present. The subrack outlet temperature sensor 114 should be located in the center of the subrack exhaust plenum 72. The subrack equipment temperature sensor 116 should be mounted to a dummy circuit card (not shown) in the electronic subrack 40 having the same thermal mass as an operational circuit card. The ambient air temperature sensor 118 should be located on a suitable exterior surface of the enclosure 20, such as in an external cavity near the inlet vent 52.

The thermal controller 100 controls the airflow through the cooling system 50, and the power of the heating element 62, to maintain the temperature of the cooling air supplied to the electronics subrack 40 within suitable thermal limits. There are preferably at least three main operational modes for the thermal controller 100 – low temperature, moderate temperature, and high temperature. The operational mode is

chosen based on the subrack inlet temperature as indicated by the subrack inlet air temperature sensor 112. For instance, the low temperature mode may apply when the subrack inlet temperature is less than 15°C, the moderate temperature mode may apply when the subrack inlet temperature is between 15°C and 35°C, and the high temperature mode may apply when the subrack inlet temperature is above 35°C.

In the low temperature mode, the fans 80 generate a constant airflow, such as 33% of capacity, while the heating element 62 is enabled. Preferably the heating element 62 is powered just enough to maintain the temperature of the air being supplied to the electronics subrack 40 just above the minimum cooling air temperature limit. In this mode, the subrack inlet temperature sensor 112 provides the primary feedback to the thermal controller 100.

In the moderate temperature mode, the heating element 62 is off, but the fans 80 are enabled. Preferably, the number and speed of the fans 80 are varied so as to maintain the temperature of the air exiting the electronics subrack 40 just below the maximum temperature limit. In order to efficiently control the airflow, it is preferred that the thermal controller 100 be able to independently control the speed of each fan 80. In this mode, the subrack inlet temperature sensor 112 provides the primary input to the thermal controller 100. The subrack outlet temperature sensor 114 is used to detect excessive temperatures in the subrack exhaust plenum and to generate an alarm.

In the high temperature mode, the heating element 62 is off, and the fans 80 operate at full capacity.

In addition, the thermal controller 100 should optionally be able to operate in a cold start mode. Cold start mode is applicable when power is first supplied to the communications electronics 34 and the temperature of the communications electronics 34, as indicated by the subrack equipment temperature sensor 116, is below the allowed minimum temperature. In this mode, the communications electronics 34 is turned off until the electronics subrack 40 can be preheated to within specification limits. During start-up, the fans 80 operate to produce a reduced airflow, such as 20%, while the heating element 62 is engaged. Preferably, the heated air within the inlet duct 56 is heated by the heating element 62 to a temperature at or near its maximum allowed temperature, such as 45°C. Heated air from the inlet duct 56 is thereby pulled through the electronics subrack 40, heating the components within the electronics subrack 40. Once the electronics subrack 40 reaches the allowed minimum temperature, the communications electronics 34 are turned on.

The functioning of the present invention may best be described in the context of cooling communications electronics 34 having specified maximum and minimum incoming cooling air temperatures, maximum cooling air temperature rise across the communications electronics 34, and a maximum cooling air exhaust temperature from the communications electronics 34. Further, the communications electronics 34 may have a limitation on the maximum rate of change in temperature for the incoming cooling air. For purposes of illustration, the following values will be used:

Incoming cooling air temperature	+5°C to 45°C
----------------------------------	--------------

heating element 62 may be disabled above 10°C for reasons described below. Above 35°C, the thermal controller 100 operates in high temperature mode, disabling power to the heating element 62 and running the fans 80 at full capacity. Between 15°C and 35°C, the thermal controller 100 operates in moderate temperature mode, disabling the heating element 62 and varying the flow rate of the fans 80 according to line "Air Flow". As shown, the airflow rate may vary non-linearly with temperature in the moderate temperature mode.

In one embodiment utilizing three main fans 80, only selected fans 80 are used at lower flow rates, with other fans 80 being activated for higher airflow rates. This method of operation is shown in Figure 7. For instance, in the low temperature mode, two fans 80 are operated at half speed and the third is off. The reason for using two fans 80 is that control of fan speed is limited to 50% - 100% by fan manufacturer design constraints. In the moderate temperature mode, two fans 80 are used with increasing speeds at the lower airflow rates, and the third fan 80 is activated at the higher airflow rates. In order to facilitate a smooth airflow transition from two to three fans 80, the speed of the first two fans 80 is reduced when the third fan 80 is turned on. After the third fan 80 is activated, all three fans 80 are ramped up in speed if additional airflow is required. If the ambient temperature begins dropping, the inverse procedure is used to transition from three fans 80 to two. Thus, in this embodiment, the airflow through the electronics subrack 40 does not change dramatically when the number operating fans 80 changes to provide increased or decreased airflow through the cooling system 50. The transition from two fans to three fans occurs at a first pre-

determined air flow rate when demand for air flow is increasing. The transition from three fans to two fans occurs at a second air flow rate when the demand for air flow is decreasing. The first air flow rate and second air flow rate are different (see Fig. 7) to prevent the fans from jittering.

By varying the operation of the heating element 62 and the fans 80 as shown in Figure 6, operation may be maintained within the thermal envelope. In addition, power consumption is substantially reduced. While the ambient temperature is lower than T_{inp} , the heating element 62 is engaged and a small flow of air is induced. However, the heating element 62 need not be fully engaged; it is only necessary that the subrack inlet temperature be at or just above the T_{inp} . Thus, heater power varies inversely with T_{amb} and stops completely when the T_{amb} is at or above T_{inp} . Further, in the moderate temperature mode, the subrack inlet temperature need only be sufficient to keep the subrack outlet temperature at or below T_{exp} . In order to maintain the subrack exit air temperature below its maximum, air flow will increase as subrack inlet temperature rises.

In addition, it should be noted that the variation in fan airflow may need to be higher than that indicated by air flow in Figure 6 when the comparison of the subrack exhaust temperature sensor 114 and the subrack inlet temperature sensor(s) 112 indicates that the temperature rise across the electronics subrack 40 is more than the allowed temperature rise. Further, the heating element 62 power and the fan 80 airflow may have to vary from the ideal represented in Figure 6 to accommodate the restriction on maximum rate of change in subrack inlet temperature. For instance, the

heating element 62 may be supplied with less power than indicated when the ambient temperature is rising rapidly in the morning after a cold night.

The present invention may, of course, be carried out in other specific ways than those herein set forth without departing from the spirit and essential characteristics of the invention. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive, and all changes coming within the meaning and equivalency range of the appended claims are intended to be embraced therein.

CLAIMS

What is Claimed is:

1. A cabinet for housing telecommunications equipment in outdoor locations comprising:
 - a) an enclosure for containing said telecommunications equipment;
 - b) an electronics subrack contained within said enclosure;
 - c) a duct for directing ambient air from outside said cabinet to said subrack, said duct including an inlet disposed adjacent a lower end of said cabinet and a subrack inlet plenum disposed adjacent an underside of said electronics subrack;
 - d) a subrack exit plenum including an outlet disposed adjacent an upper side of said electronics subrack;
 - e) at least one fan for drawing ambient air into said inlet, through said duct into said subrack inlet plenum, through said electronics subrack into said subrack exit plenum, and through said outlet out of said enclosure.
2. The cabinet of claim 1 wherein said duct includes a heating chamber between said inlet and said subrack inlet plenum.
3. The cabinet of claim 2 further including a heating element disposed within said heating chamber for heating ambient air drawn in through said inlet.
4. The cabinet of claim 3 wherein said heating element is an electric resistance heater.

5. The cabinet of claim 3 further including a thermal controller for controlling power to said heating element and said air flow according to a predetermined control scheme.

6. The cabinet of claim 4 wherein, in a low temperature mode, said thermal controller maintains air flow constant and varies power to said heating element.

7. The cabinet of claim 6 wherein, in a moderate temperature mode, said thermal controller varies said air flow and shuts off power to said heating element.

8. The cabinet of claim 7 wherein said air flow is varied non-linearly in said moderate temperature mode.

9. The cabinet of claim 7 wherein said air flow is varied in said moderate temperature mode so as to maintain outlet temperature constant within the operational limits of the fan.

10. The cabinet of claim 7 wherein, in a high temperature mode, the thermal controller shuts off power to said heating element and operates said fan at maximum capacity.

11. The cabinet of claim 5 wherein said thermal controller operates said heating element and said fan to maintain the rate of change of temperature in said subrack inlet plenum to less than .5°C per minute.

12. A cabinet for housing telecommunications equipment in outdoor locations comprising:

- a) an enclosure for containing said telecommunications equipment;
- b) an electronics subrack contained within said enclosure;
- c) an inlet opening disposed in a lower end of said cabinet below said subrack to allow ambient air to enter said enclosure;
- d) an outlet opening disposed in an upper portion of said cabinet above said subrack to expel air from said cabinet;
- e) at least one fan for drawing ambient air into said inlet, through said subrack and out of said outlet opening;
- f) a heating element for heating ambient air drawn in through said inlet before the air reaches said subrack;
- g) a thermal controller for controlling the operation of said heating element and said fan to maintain the temperature within said enclosure within a predetermined thermal envelope;
- h) wherein said thermal controller is operative to maintain air flow constant and vary power to said heating element at ambient temperatures in a low temperature mode, and shut off power to said heating element and to vary said air flow in a moderate temperature mode.

13. The cabinet of claim 12 wherein said air flow is varied non-linearly over a range of temperatures in said moderate temperature mode.

14. The cabinet of claim 12 wherein said air flow is varied in said moderate temperature mode so as to maintain outlet temperature constant within the operational limits of the fan.

15. The cabinet of claim 12 wherein said thermal controller operates said heating element and said fan to maintain the rate of change of temperature in said subrack plenum to less than .5°C per minute.

16. The cabinet of claim 12 further including a duct within said cabinet to direct air from said inlet opening to said subrack.

17. The cabinet of claim 16 wherein said duct includes a heating chamber and wherein said heating element is disposed in said heating chamber.

18. The cabinet of claim 12 wherein said heating element is an electrical resistance heater.

19. A method for controlling the temperature in an outdoor telecommunications cabinet having an electronic subrack comprising:

- a) maintaining a nearly constant air flow through said subrack at ambient temperatures below a first temperature;
- b) heating said air flow at ambient temperatures below said first temperature so as to maintain the temperature at an inlet to the subrack constant over a first range of ambient temperatures up to said first temperature;

- c) maintaining a nearly constant air flow through said subrack at temperatures above said first temperature and below a second temperature;
- d) shutting off said heating element at ambient temperatures above said first temperature;
- e) varying the air flow through said subrack at ambient temperatures above said second temperature so as to maintain the temperature of the air flow at said outlet relatively constant over a second range of ambient temperatures above said second temperature.

20. The method of claim 19 wherein said air flow is varied non-linearly above said second temperature.

21. The method of claim 19 wherein said air flow and heating element are controlled so as to maintain the rate of change of the temperature at the inlet to the subrack within approximately .5°C per minute.

22. A method for controlling the temperature in an outdoor telecommunications cabinet having an electronic subrack comprising:

- a) maintaining a nearly constant air flow through said subrack at ambient temperatures below a first temperature;
- b) heating said air flow at ambient temperatures below said first temperature so as to maintain the temperature at an inlet to the subrack constant over a first range of ambient temperatures up to said first temperature;

- c) varying the air flow through said subrack at ambient temperatures above a second temperature so as to maintain the temperature of the air flow at said outlet relatively constant over a second range of ambient temperatures above said second temperature.

23. The method of claim 22 wherein said air flow and heating element are controlled so as to maintain the rate of change of the temperature at the inlet to the subrack within approximately .5°C per minute.

24. A method for cold-starting a telecommunications equipment contained within a cabinet, comprising:

- a. inducing an airflow within said cabinet and through said equipment;
- b. heating said airflow at a point upstream from said telecommunications equipment;
- c. monitoring the temperature of the telecommunications equipment;
- d. providing power to said telecommunications equipment when the temperature of the telecommunications equipment reaches a predetermined temperature.






FIG. 1








Fig.4




FIG. 5




FIG. 6




Fig. 7

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/23492

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : A21B 01/00; H05B 01/00, 03/10; H05K 05/00, 07/16; F26B 21/06

US CL : Please See Extra Sheet.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : Please See Extra Sheet.

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim
X, P	US 5,899,001 A (LAYTON) 04 May 1999, Fig.1.	1-4
Y, P		5, 19, 22, 24
Y	US 5,228,212 A (TURETTA et al) 20 July 1993, Fig.1, col.3, lines 41, 45-46.	5, 19, 22, 24
X	US 4,860,163 A (SARATH) 22 August 1989, Fig. 2.	1
A	US 5,781,410 A (KEOWN et al) 14 July 1998.	1
A	US 5,398,159 A (ANDERSSON et al) 14 May 1995.	1
A	US 5,801,632 A (OPAL) 01 September 1998.	1-4

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combinations being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

10 DECEMBER 1999

Date of mailing of the international search report

24 FEB 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

Fadi H. Dahbour *Diane Smith*

Telephone No. (703) 308-0861

INTERNATIONAL SEARCH REPORTInternational application No.
PCT/US99/23492**C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4,935,604 A (Allen et al) 19 June 1990, Fig.7, col.7, lines 42-43.	6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/23492

A. CLASSIFICATION OF SUBJECT MATTER:

US CL :

219/209, 210, 400, 553

361/724, 727

34/76, 77

B. FIELDS SEARCHED

Minimum documentation searched

Classification System: U.S.

219/209, 210, 400, 553, 385, 521

361/724, 727

34/76, 77

392/379, 383

312/236